

Manufacturer of TFE-O-SIL®O-Rings & Gaskets Since 1976 FEP & PFA Encapsulated Silicone, Flouroelastomer & EPDM

EPDM - 70 DUROMETER

USP Class VI compliant - Peroxide Cured FDA Conforming - Title 21 CFR 177.2600 3A Sanitary Standard compliant

Original Properties	ASTM D2000 Test Method	Requirement	Result
Durometer, Shore A	D2240	70 <u>+</u> 5	73
Tensile strength, psi	D 412	1450	1700
Elongation, %	D 412	250	310
Heat Aged 70 Hours @ 100°C (212°F)			
Durometer change, pts., max.	D2240	<u>+</u> 10	+ 1
Tensile change, %, max.	D 573	- 25	- 4
Elongation change, %, max.	D 573	- 25	-21
Compression Set 22 Hours @ 100°C (212°F)			
% of original deflection, max.	D 395	35	27.0
Low Temperature Brittlenes	ss		
3 minutes @ -55°C	D2137	non-brittle	Pass
Temperature Range °C (°F)	-54° to + 175°C (-65° to + 350°F)		

729 W. Winthrop Avenue • Addison, IL 60101 Phone: 800-770-7128 / 630-628-9221 • Fax: 630-628-9229 Web: <u>www.row-inc.com</u> • Email: <u>sales@row-inc.com</u>

II Hot water & steam service to 162°C (325°F)

Temperature Information - EPDM O-Rings and Adhesives

The service temperature range of the EPDM elastomer conforming to the USP Class VI requirements is: -65° to +300° F

Regarding the adhesive used to bond the ends of the cord:

- 1. The USP Class VI approved adhesive will lose tensile strength as the service temperature increases. It will lose 50% of its tensile strength at 212° F and up to 75% of its tensile at its upper service temperature of 300° F.
- 2. If our standard FDA approved adhesive were used, at least 75% of its tensile strength would be maintained at the elastomer upper service limit of 300° F.

Summary:

In order for the elastomer and adhesive to be USP Class VI approved, there would be a compromise in the tensile strength of the joint at elevated temperature (175° F and above). If the integrity of the joint is critical, and service temperatures will exceed 212° F, we would suggest using our standard FDA adhesive.

If the USP Class VI approval is required in its entirety, the maximum recommended service temperature for our EPDM vulcanized O-Rings would be +225°F